

Adjustable 3 wings roof attic ventilator for sloped roof OPTI-A312

The OPTI-A312 slope attic vent with a 12" design combined with 3 fins and openings allow for optimal ventilation of the attic. Openings shaped from the structure of the vent eliminate any need for long-term maintenance and prevent the intrusion of birds and rodents inward. The anti-gust deflectors prevent the elements from penetrating regardless of the wind direction. This vent provides a cooler attic in the summer months as well as a drier one in the winter months. It thus extends the integrity of the structure allowing for optimal comfort inside and delivering energy savings. This static vent, with the help of the wind, produces a chimney effect. The air is exchanged continuously at a frequency of 266 ft³/min. This model can ventilate up to 825 sq. ft.



Advantages

- Optimizes and evenly tempers attic ventilation
- Facilitates the evacuation of heat and condensation
- Preserves the integrity of attic materials
- Easy to adjustment on a slope from 2/12 to 18/12
- Easy to install by only one person
- Screws included
- Anti-gust deflector
- No maintenance and noise free

Colours

Standard colours available: brown, grey, black and charcoal. Other colours available on special order (additional fee).

Norms


CSA Certified
The National Building Code requires adequate ventilation of the roof as per the minimum standard of Section 9.19.1 or according to the ACNOR CAN3-A93-M82.

Use

Ventilation is required by the Canadian Building Code. A good ventilation means keeping the attic space near the outside temperature to avoid excessive contrasts. With the help of soffits, for example In summer, the chimney effect created by the Optimum ventilator eliminates excess heat from the attic and thus helps maintain the integrity of the asphalt shingles. In winter, you will get a drier attic. No matter what the season, Optimum Ventilators will help to optimize the comfort of your home!

Characteristics

The vent is manufactured from galvanized steel followed by a specialized baked paint finish.



PRODUCT	DIMENSIONS				EVACUATION	NUMBER OF DEFLECTORS	STEEL GAUGE USED
	A	B	C	D			
OPTI-A312	30,4 cm • 12"	49,5 cm • 19,5"	27,9 cm • 11"	33,2 cm • 13"	0,06 m ² • 99 in. ²	3	22 - 24 & 26

Custom model

Custom models are available as special order. *We can manufacture any other size on request.

Options

This model is available with or without filter. If you have a ventilator with a filter, you must install a water collecting tray. At all times, it is strongly recommended to install a water collecting tray (OPTI-PAN) under your ventilator, it is the solution for a dry attic.

Warranty

The consumer must ensure that this product is appropriate for the intended use. Since the installer's skills and surface conditions are independent of the manufacturer's control, we limit our liability to the replacement of defective equipment only if proof of purchase can be provided. Free on board (FOB factory).